

TERRA 2200



Design	Pepe Comi	
Material	100% Polyester / Aluminium <1%	
Width	3000mm (+/- 1%)	
Care Instructions	Refer to inside cover for details	
Weight	130g/m ² (+/- 5%)	
Thickness	0.34mm	
Standard Roll Length	50mtrs	
Breaking Strength (ISO 13934-1)	Warp: 300 N	Weft: 400 N
Elongation To Break (ISO 13934-1)	Warp: 18-20%	Weft: 20-22%
Fastness To Light (ISO 105B02 - Bluescale 1-8)	Aluminium Side: Class 7	Colour Side: Class 5
Flame Retardant According To	DIN 4102 (B1) / BS 5867: Part 2 1980 (1993) Type B EN 13773 Class 1 / IMO A.563(14)	

USAGE					Maximum Drop
	Panel	Roller (Normal Rolling)	Roller (Reversed Rolling)	Roman	
Vertical Stripes	Yes	Yes	Yes	Yes	Unlimited
Horizontal Stripes	Not Recommended	Yes	Not Recommended	Yes	3000mm

N.B. - All articles for indoor use behind glass. The aluminium side of the screen should always face the window



FR = Fire Retardancy / 5 = 5 Year Warranty

Exclusive distributors of **svensson markspelle** **erco systems ab**



livingshade.com.au

3/43 Leighton Place, Hornsby NSW 2077 Australia
Tel: +612 9477 6955 Fax: +612 9477 5506
sales@livingshade.com.au

TERRA 2200	Solar optical properties (%) according to EN 14500						Thermal performance according to EN 14501							
	Ts	Rs	As	Tv	Tuv	O-F	Glazing A		Glazing B		Glazing C		Glazing D	
Colour							Gtot	U	Gtot	U	Gtot	U	Gtot	U
8000 WHITE	4	73	23	4	1	0	0.22	2.6	0.26	1.8	0.32	0.95	0.16	0.90
6600 DUNE	3	71	26	3	1	0	0.23	2.6	0.28	1.8	0.33	0.95	0.17	0.90
6800 COCO	1	67	32	1	0	0	0.25	2.6	0.29	1.8	0.34	0.95	0.17	0.90
8400 OYSTER	3	68	29	2	0	0	0.24	2.6	0.29	1.8	0.34	0.95	0.17	0.90
8900 BLACK	0	64	36	0	0	0	0.26	2.6	0.31	1.8	0.35	0.95	0.18	0.90

All colours are representative only, dye lot variations can occur.

Ts = Solar Transmission Rs = Solar Reflection As = Solar Absorption
Tv = Visible Light Transmission Tuv = Ultraviolet Transmission O-F = Openness Factor

Gtot = Total Solar Energy Transmittance (0-1) 1=100%

U = Thermal Transmittance W/m²=K

Glazing A = Clear Single Glazing, G=0.85, U=5.8

Glazing B = Clear Double Glazing, G=0.76, U=2.9

Glazing C = Double Glazing With Low E Coating, G=0.59, U=1.2

Glazing D = Reflective Double Glazing With Low E Coating, G=0.32, U=1.1

All articles for indoor use behind glass.



Blockout Aluminium

Care Instructions

Please read full care instructions details prior to usage of any fabrics, available from Living Shade.