

# VOLT 2150



Design	Pepe Comi	
Material	100% Polyester / Aluminium <1%	
Width	3000mm (+/- 1%)	
Care Instructions	Refer to inside cover for details	
Weight	122g/m <sup>2</sup> (+/- 5%)	
Thickness	0.34mm	
Standard Roll Length	50mtrs	
Breaking Strength (ISO 13934-1)	Warp: 300 N	Weft: 400 N
Elongation To Break (ISO 13934-1)	Warp: 18-20%	Weft: 20-22%
Fastness To Light (ISO 105B02 - Bluescale 1-8)	Aluminium Side: Class 7	Colour Side: Class 5
Flame Retardant According To	DIN 4102 (B1) / BS 5867: Part 2 1980 (1993) Type B EN 13773 Class 1 / IMO A.563(14)	

USAGE					Maximum Drop
	Panel	Roller (Normal Rolling)	Roller (Reversed Rolling)	Roman	
Vertical Stripes	Yes	Yes	Yes	Yes	Unlimited
Horizontal Stripes	Not Recommended	Yes	Not Recommended	Yes	3000mm

N.B. - All articles for indoor use behind glass. The aluminium side of the screen should always face the window



FR = Fire Retardancy / 5 = 5 Year Warranty

Exclusive distributors of **svensson markspelle** **erco systems ab**



livingshade.com.au

3/43 Leighton Place, Hornsby NSW 2077 Australia  
Tel: +612 9477 6955 Fax: +612 9477 5506  
sales@livingshade.com.au

VOLT 2150	Solar optical properties (%) according to EN 14500						Thermal performance according to EN 14501							
							Glazing A		Glazing B		Glazing C		Glazing D	
Colour	Ts	Rs	As	Tv	Tuv	O-F	Gtot	U	Gtot	U	Gtot	U	Gtot	U
8000 WHITE	17	64	19	16	11	7	0.31	2.7	0.34	1.9	0.36	0.98	0.19	0.92
6600 DUNE	15	62	23	14	10	7	0.31	2.7	0.35	1.9	0.37	0.98	0.19	0.92
6800 COCO	11	58	31	10	8	7	0.33	2.7	0.36	1.9	0.38	0.98	0.20	0.92
8400 OYSTER	14	60	26	12	9	7	0.32	2.7	0.35	1.9	0.38	0.98	0.19	0.92
8900 BLACK	7	55	38	7	7	6	0.33	2.7	0.37	1.9	0.39	0.98	0.20	0.92

All colours are representative only, dye lot variations can occur.

Ts = Solar Transmission      Rs = Solar Reflection      As = Solar Absorption  
Tv = Visible Light Transmission      Tuv = Ultraviolet Transmission      O-F = Openness Factor

Gtot = Total Solar Energy Transmittance (0-1) 1=100%

U = Thermal Transmittance W/m<sup>2</sup>=K

Glazing A = Clear Single Glazing, G=0.85, U=5.8

Glazing B = Clear Double Glazing, G=0.76, U=2.9

Glazing C = Double Glazing With Low E Coating, G=0.59, U=1.2

Glazing D = Reflective Double Glazing With Low E Coating, G=0.32, U=1.1

All articles for indoor use behind glass.



Open      Blockout Aluminium

## Care Instructions

Please read full care instructions details prior to usage of any fabrics, available from Living Shade.